



MULTI-SPLIT HI-WALL

INDOOR UNIT

N3KV2



Toshiba IAQ
filtration system

This elegant unit combines an improved energy efficiency with indoor air quality in single and/or multi split applications.

Memorization of the desired operation parameters with one touch of "my comfort" button.

Self cleaning function to remove moisture from the internal components of the unit.

Modern stylish and compact design.

N3KV2

Physical data Indoor unit

Indoor unit	RAS-		M07N3KV2-E	B10N3KV2-E	B13N3KV2-E	B16N3KV2-E	B22N3KV2-E	M24N3KV2-E
Air Flow (max)	m ³ /h - l/s	C	516 - 143	516 - 143	570 - 158	684 - 190	1080 - 300	1134 - 315
Sound pressure level (h/l)	dB(A)	C	38/26	38/26	39/26	45/30	47/35	49/37
Sound power level (h)	dB(A)	C	53	53	54	60	60/48	62/50
Air Flow (max)	m ³ /h - l/s	H	570 - 158	570 - 158	624 - 173	738 - 206	1098 - 305	1152 - 320
Sound pressure level (h/l)	dB(A)	H	39/28	39/28	40/28	45/31	47/35	49/37
Sound power level (h/l)	dB(A)	H	54	54	55	60	60/48	62/50
Dimensions (HxWxD)	mm		275x790x225	275x790x225	275x790x225	275x790x225	320x1050x243	320x1050x243
Weight	kg		10	10	10	10	13	13
Flare connections (gas - liquid)	inch		3/8 - 1/4	3/8 - 1/4	3/8 - 1/4	1/2 - 1/4	1/2 - 1/4	1/2 - 1/4

C = cooling mode H = heating mode h/l = high / low speed