

MULTI-SPLIT CONSOLE

INDOOR UNIT

UFV



Floor heating function



Unique floor heating function, to deliver a powerful flow at floor level for a uniform and comfortable room heating.

Innovative and compact unit to be installed on the floor and in low wall applications, fit perfectly under the window sills or in a low ceiling attic.

Compact and modern design in all three dimensions (60x70x22 cm).

Toshiba IAQ filtration system.

Child lock function on the unit display panel.

Brightness level control of the display unit to reduce the led light glow.

Automatic restart function in case of unexpected electricity supply line power cuts.

UFV

Physical data Indoor unit

Indoor unit	HP		RAS-B10UFV-E1	RAS-B13UFV-E1	RAS-B18UFV-E1
Air Flow (max)	m ³ /h - l/s	C	468 - 130	510 - 142	600 - 167
Sound pressure level (h/l)	dB(A)	C	39/26	40/27	46/34
Sound power level (h)	dB(A)	C	54	55	61
Air Flow (max)	m ³ /h - l/s	H	510 - 142	552 - 153	642 - 178
Sound pressure level (h/l)	dB(A)	H	39/26	40/27	46/34
Sound power level (h)	dB(A)	H	54	55	61
Dimensions (HxWxD)	mm		600x700x220	600x700x220	600x700x220
Weight	kg		16	16	16
Flare connections (gas - liquid)	inch		3/8 - 1/4	3/8 - 1/4	1/2 - 1/4

C = cooling mode H = heating mode h/l = high / low speed