

Appliance - Split type air conditioner

Directive 2009/125/EC

Supplier	Toshiba Carrier Corporation
Outdoor unit	RAS-18J2AVSG-E
Indoor unit	RAS-B18J2FVG-E

Refrigerant

Type	R32
Global Warming Potential	GWP kgCO ₂ eq 675

Refrigerant leakage contributes to climate change. Refrigerant with lower global warming potential (GWP) would contribute less to global warming than a refrigerant with higher GWP, if leaked to the atmosphere. This appliance contains a refrigerant fluid with a GWP equal to 1975. This means that if 1 kg of this refrigerant fluid would be leaked to the atmosphere, the impact on global warming would be 1975 times higher than 1 kg of CO₂, over a period of 100 years. Never try to interfere with the refrigerant circuit yourself or disassemble the product yourself and always ask a professional

Sound power level

		Cooling	Heating
Outdoor unit	dB	63	63
Indoor unit	dB	59	60

Cooling

Energy efficiency class		A++
Design load	P _{designc} kW	5.0
Seasonal efficiency	SEER	6.80
Seasonal electricity consumption (*)	Q _{ce} kWh/annum	257

Heating

		Average climate	Colder climate	Warmer climate
Energy efficiency class		A++	-	A+++
Design load	P _{designh} kW	4.0	-	2.2
Seasonal efficiency	SCOP	4.60	-	6.30
Seasonal electricity consumption (*)	Q _{he} kWh/annum	1217	-	482
Back up heating capacity	kW	0.740	-	0.000

Declared capacity for heating, at indoor temperature 20°C and outdoor temperature T_j.

T _j = -7 °C	P _{dh} kW	3.54	-	-
T _j = +2 °C	P _{dh} kW	2.15	-	2.15
T _j = +7 °C	P _{dh} kW	1.38	-	1.38
T _j = +12 °C	P _{dh} kW	1.38	-	1.38
T _j = bivalent temperature	P _{dh} kW	3.54	-	2.15
T _j = operation limit temperature	P _{dh} kW	2.80	-	2.80

(*) Based on standard test results. Actual energy consumption will depend on how the appliance is used and where it is located

Contact details

Toshiba Carrier Europe S.A.S
Route de Thil, 01120, Montluel, France